

## Han 10B-HTE/HSE-M32/32



Image is for illustration purposes only. Please refer to product description.

Part number	19 30 010 0599
Specification	Han 10B-HTE/HSE-M32/32
HARTING eCatalogue	<a href="https://b2b.harting.com/19300100599">https://b2b.harting.com/19300100599</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> B
Type of hood/housing	Hood
Type	High construction

### Version

Size	10 B
Version	Top/side entry
Cable entry	1x M32 1x M32
Locking type	Double locking lever
Field of application	Standard hoods/housings for industrial connectors

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP66 IP67
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Aluminium die-cast
-------------------------	--------------------



**Pushing Performance**  
Since 1945

## Material properties

Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

## Specifications and approvals

Approvals	DNV GL
CE	Yes

## Commercial data

Packaging size	1
Net weight	140.1 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140164475
eCl@ss	27440202 Shell for industrial connectors