

Han 10B-kg-QB-M25



| Part number | 19 30 010 0736 |
|--------------------|-------------------------------------|
| Specification | Han 10B-kg-QB-M25 |
| HARTING eCatalogue | https://b2b.harting.com/19300100736 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|----------------------------------|---|
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Cable to cable housing |
| Туре | High construction |
| | |
| Version | |
| Size | 10 B |
| Version | Top entry |
| Cable entry | 1x M25 |
| Locking type | Double locking lever |
| Han-Easy Lock [®] | Yes |
| Field of application | Standard hoods/housings for industrial connectors |
| | |
| Technical characteristics | |
| Limiting temperature | -40 +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-------------------------|--------------------|
| | |

Page 1 / 3 | Creation date 2023-03-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

| Surface (hood/housing) | Powder-coated |
|--|---|
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate (PC) Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |
| ECHA SCIP number | 16ca3004-52e6-46fa-bf13-9c1e1b30f813 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Naphthalene |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|-----------|--|
| CE | Yes |
| Approvals | DNV GL |

Commercial data

| Packaging size | 1 |
|--------------------------------|---------------|
| Net weight | 200 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140125520 |

Page 2 / 3 | Creation date 2023-03-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 19 30 010 0736 Han 10B-kg-QB-M25



Commercial data

eCl@ss

27440202 Shell for industrial connectors

Page 3 / 3 | Creation date 2023-03-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany