



Pushing Performance  
Since 1945

## Han 48 B-HTE5-f. SL.M25



Part number	19 30 048 0496
Specification	Han 48 B-HTE5-f. SL.M25
HARTING eCatalogue	<a href="https://b2b.harting.com/19300480496">https://b2b.harting.com/19300480496</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han® B
Type of hood/housing	Hood
Type	High construction

### Version

Size	48 B
Version	Top entry
Cable entry	5x M25
Locking type	Single locking lever
Field of application	Standard hoods/housings for industrial connectors

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)



**Pushing Performance**  
Since 1945

## Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

## Commercial data

Packaging size	1
Net weight	720 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140165472
eCl@ss	27440202 Shell for industrial connectors