

Han 6B-HMC-HSE-R-M25



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 30 206 0546 |
| Specification | Han 6B-HMC-HSE-R-M25 |
| HARTING eCatalogue | https://b2b.harting.com/19302060546 |

Version

| | |
|----------------------|---|
| Size | 6 B |
| Version | Side entry |
| Cable entry | 1x M25 |
| Locking type | Single locking lever |
| Field of application | Special hoods and housings for high mating cycles |

Technical characteristics

| | |
|---|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Mating cycles with other HMC components | ≥10,000 |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| | |
|-----------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|----------------------------|
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R1 (HL 1-3) R7 (HL 1-3) |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 115 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140170803 |
| eCl@ss | 27440202 Shell for industrial connectors |