

Han 16HP Direct/EMC-PFT-Housing-TE-M40



Part number	19 39 816 1123
Specification	Han 16HP Direct/EMC-PFT-Housing-TE- M40
HARTING eCatalogue	https://b2b.harting.com/19398161123

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] HP Direct EMC
Type of hood/housing	Panel feed through housing
Version	
Size	16 B
Cable entry	1x M40
Locking type	Screw locking
Technical characteristics	
Tightening torque (screw locking)	4 Nm
Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
	IP66 IP68
Degree of protection acc. to IEC 60529	IP69 / IPX9K acc. to ISO 20653
Material properties	

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Electrical conductive
Colour (hood/housing)	Unpainted
Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant

Page 1 / 2 | Creation date 2022-12-28 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
CE	Yes

Commercial data

Packaging size	1
Net weight	631 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140183155
eCl@ss	27440202 Shell for industrial connectors