

Han-Eco Mod.6-HSE-M32



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 41 006 0522 |
| Specification | Han-Eco Mod.6-HSE-M32 |
| HARTING eCatalogue | https://b2b.harting.com/19410060522 |

Version

| | |
|--------------|----------------------|
| Size | 6 B |
| Module slots | 3 |
| Version | Side entry |
| Cable entry | 1x M32 |
| Locking type | Double locking lever |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Number of relockings | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| | |
|---|--|
| Material (hood/housing) | Polyamide (PA) Fibre-glass reinforced |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |



Pushing Performance
Since 1945

Material properties

Fire protection on railway vehicles EN 45545-2 (2020-08)

Requirement set with Hazard Levels R22 (HL 1-3)
R23 (HL 1-3)

Specifications and approvals

Specifications IEC 61984
EN 45545-2 Fire protection on railway vehicles

UL / CSA UL 1977 ECBT2.E235076
CSA-C22.2 No. 182.3 ECBT8.E235076

CE Yes

Commercial data

Packaging size 1

Net weight 101 g

Country of origin Germany

European customs tariff number 85389099

GTIN 5713140130760

eCl@ss 27440202 Shell for industrial connectors