

Han-Eco 6B-HSM1-with SL-M25-glanded



| Part number | 19 43 106 0251 |
|--------------------|-------------------------------------|
| Specification | Han-Eco 6B-HSM1-with SL-M25-glanded |
| HARTING eCatalogue | https://b2b.harting.com/19431060251 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|-----------------------------|-----------------------------|
| Series of hoods/housings | Han-Eco [®] B |
| Type of hood/housing | Surface mounted housing |
| Description of hood/housing | With integrated cable gland |

Version

| Size | 6 B |
|--------------|----------------------|
| Version | Side entry |
| Cable entry | 1x M25 |
| Locking type | Single locking lever |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|--|
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Number of relockings | ≥500 |
| Degree of protection acc. to IEC 60529 | IP66 |
| Clamping range | 9 17 mm |

Material properties

| Material (hood/housing) | Polyamide (PA) Fibre-glass reinforced |
|-------------------------|---------------------------------------|
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |



Material properties

| Colour (seal) | RAL 9005 (jet black) |
|--|--|
| Material (locking) | Polyamide (PA) Fibre-glass reinforced |
| Colour (locking) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead |
| ECHA SCIP number | be45dcda-0f90-459a-a8bc-78fb7986a295 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| Specifications | IEC 61984 EN 45545-2 Fire protection on railway vehicles |
|----------------|---|
| CE | Yes |

Commercial data

| 1 |
|--|
| 211 g |
| Germany |
| 85389099 |
| 5713140177031 |
| 27440202 Shell for industrial connectors |
| |