

## Han1A CA 3+PE -latch m/- PVC 10m



Image is for illustration purposes only. Please refer to product description.

Part number	33 50 040 0201 100
Specification	Han1A CA 3+PE -latch m/- PVC 10m
HARTING eCatalogue	<a href="https://b2b.harting.com/33500400201100">https://b2b.harting.com/33500400201100</a>

### Identification

Category	System cabling
Series	Han <sup>®</sup> 1A
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	Han <sup>®</sup> 1A Male
Type of cable	Copper cable (round)
Description of the cable	Oil resistant

### Version

Cable length	10 m
Number of cores	4
Core structure	4x 2.5 mm <sup>2</sup>
Number of contacts	3
PE contact	Yes
Locking type	Snap-in latches

### Technical characteristics

Rated current	16 A
Rated voltage	400 V
Rated voltage conductor-earth	300 V
Limiting temperature	-40 ... +80 °C unmoved -15 ... +80 °C moved
Mating cycles	≥100



**Pushing Performance**  
Since 1945

## Technical characteristics

Degree of protection acc. to IEC 60529 IP65

Cable diameter 9.2 mm

## Material properties

Material (cable) PVC

Colour (cable) Grey

## Specifications and approvals

Specifications IEC 60332-1-2 Flame retardancy

## Commercial data

Packaging size 1

Country of origin Romania

European customs tariff number 85444290

GTIN 5713140237186

eCl@ss 27060311 Assembled sensor actuator-line