

## Han1A CA 12 Pole +latch f/- PVC 1m



Image is for illustration purposes only. Please refer to product description.

Part number	33 50 150 0304 010
Specification	Han1A CA 12 Pole +latch f/- PVC 1m
HARTING eCatalogue	<a href="https://b2b.harting.com/33501500304010">https://b2b.harting.com/33501500304010</a>

### Identification

Category	System cabling
Series	Han <sup>®</sup> 1A
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	Han <sup>®</sup> 1A Female
Type of cable	Copper cable (round)
Description of the cable	Oil resistant

### Version

Cable length	1 m
Number of cores	12
Core structure	12x 0.34 mm <sup>2</sup>
Number of contacts	12
Locking type	Snap-in latches

### Technical characteristics

Rated current	6.5 A
Rated voltage	50 V
Limiting temperature	-30 ... +80 °C unmoved -5 ... +80 °C moved
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65



Pushing Performance  
Since 1945

## Technical characteristics

Cable diameter	7.8 mm
----------------	--------

## Material properties

Material (cable)	PVC
Colour (cable)	Grey
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead
ECHA SCIP number	a37d5146-999a-4b9a-b795-2f24e0cbb884
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

## Specifications and approvals

Specifications	IEC 60332-1-2 Flame retardancy
----------------	--------------------------------

## Commercial data

Packaging size	1
Net weight	120 g
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140238084
eCl@ss	27060311 Assembled sensor actuator-line