

Han1A CA 12 Pole +latch m/- PVC 7,5m



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 33 50 160 0304 075 |
| Specification | Han1A CA 12 Pole +latch m/- PVC 7,5m |
| HARTING eCatalogue | https://b2b.harting.com/33501600304075 |

Identification

| | |
|--------------------------|---------------------------|
| Category | System cabling |
| Series | Han [®] 1A |
| Element | Cable assemblies |
| Specification | Pre-assembled on one side |
| Connector 1 | Han [®] 1A Male |
| Type of cable | Copper cable (round) |
| Description of the cable | Oil resistant |

Version

| | |
|--------------------|--------------------------|
| Cable length | 7.5 m |
| Number of cores | 12 |
| Core structure | 12x 0.34 mm ² |
| Number of contacts | 12 |
| Locking type | Snap-in latches |

Technical characteristics

| | |
|--|---|
| Rated current | 6.5 A |
| Rated voltage | 50 V |
| Limiting temperature | -30 ... +80 °C unmoved -5 ... +80 °C moved |
| Mating cycles | ≥100 |
| Degree of protection acc. to IEC 60529 | IP65 |



Pushing Performance
Since 1945

Technical characteristics

| | |
|----------------|--------|
| Cable diameter | 7.8 mm |
|----------------|--------|

Material properties

| | |
|------------------|------|
| Material (cable) | PVC |
| Colour (cable) | Grey |

Specifications and approvals

| | |
|----------------|--------------------------------|
| Specifications | IEC 60332-1-2 Flame retardancy |
|----------------|--------------------------------|

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Country of origin | Romania |
| European customs tariff number | 85444290 |
| GTIN | 5713140237551 |
| eCl@ss | 27060311 Assembled sensor actuator-line |