

## Han F+B CA 17D 0,5mm<sup>2</sup> f/- st/- PUR 5,0m



Image is for illustration purposes only. Please refer to product description.

Part number	33 50 420 0306 050
Specification	Han F+B CA 17D 0,5mm <sup>2</sup> f/- st/- PUR 5,0m
HARTING eCatalogue	<a href="https://b2b.harting.com/33504200306050">https://b2b.harting.com/33504200306050</a>

### Version

Cable length	5 m
Number of cores	17
Core structure	0.5 mm <sup>2</sup>
Number of contacts	17
PE contact	Yes

### Technical characteristics

Rated current	10 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Limiting temperature	-20 ... +80 °C moved -40 ... +80 °C unmoved
Degree of protection acc. to IEC 60529	IP69
Minimum bending radius	10x Cable diameter (repeated bending) 5x Cable diameter (singular bending)

### Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Grey



**Pushing Performance**  
Since 1945

## Specifications and approvals

Specifications	EN 50525-1
	IEC 60228
	EN 50363-3
	EN 50363-10-2
Approvals	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topactive OKTO
	Ecolab Topax 66
	Ecolab Topax 990

## Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140238206
eCl@ss	27060311 Assembled sensor actuator-line