

InduCom 9p 1T-entry kn-screw 4-40

		Part number	61 03 001 0010 160
		Specification	InduCom 9p 1T-entry kn-screw 4-40
		HARTING eCatalogue	https://b2b.harting.com/61030010010160
Version			
Size	D-Sub 1		
Cable entry	1x		
Strain relief	An additional InduCom cable clamp or a crimp flange - ferrule combination is available dependant on the use of the cable.		
Locking type	Knurled screw Thread 4-40 UNC		
ground connection	With internal grounding block		
2 parts	Yes		
Separable	Yes		

Technical characteristics

Tightening torque	0.4 Nm ground connection
	0.4 Nm cover screw
	0.4 Nm Locking screw
Ambient temperature	-55 +125 °C
Degree of protection acc. to IEC 60529	IP30

Material properties

Material (hood/housing)	Zinc die-cast
Material (screw)	Steel, nickel plated
Length	38.6 mm
Width	31 mm
Height	14.8 mm
Commercial data	
Packaging size	1

Page 1 / 2 | Creation date 2023-03-02 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 61 03 001 0010 160 InduCom 9p 1T-entry kn-screw 4-40



Commercial data

Net weight	40 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140222557
eCl@ss	27440213 D-Sub hood

Page 2 / 2 | Creation date 2023-03-02 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany