

Part number

MAPN 06 L32



Surface mounting housing, LS-TYPE series, with 1 lever, M32 cable entry, size "44.27", high construction

Product description

Product type	Surface mounting housing
Series	LS-TYPE
Closing type	With 1 lever
Size	Size "44.27"
Cable entry	M32
Specification	High construction

Technical data

IP degree of protection	IP65 / IP66 / IP69
--------------------------------	--------------------

Further technical details

Weight	300,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163118
eCl@ss 8.1	27440202
ETIM 7.0	EC000437


Packaging Information

Packaging length	475,00 mm
Packaging height	200,00 mm
Packaging width	150,00 mm
Packaging weight	3,20 kg
Packaging volume	14,25 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747248778
Sub-packaging weight	1,60 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187640

Part number MAPN 06 L32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "44.27" **LS-TYPE version**

inserts:	page	housings with single lever	hoods with 2 pegs	
CDD	24 poles + @ 59 *			
CQE	10 poles + @ 80 *			
CSH	6 poles + @ 88 *			
CCE	6 poles + @ 94 *			
CNE, CSE, JCNE, JCSE	6 poles + @ 95 and 106 *			
CSS	6 poles + @ 118 *			
CTE, CTSE **)	6 poles + @ 126 *			
MIXO	2 modules 160+195 *			
insert centre distance: 44 x 27 mm				
* refer to catalogue page CN.12				
description	part no.	entry M	part no.	entry M
bulkhead mounting housing, with lever	CHIN 06 L			
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry, high construction			MHON 06 L25	25
with pegs, top entry, high construction			MFON 06 L25	25
with pegs, top entry, high construction			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25
**) only in the CHIN 06 L enclosure				
panel cut-out for bulkhead mounting housing in mm	dimensions in mm		dimensions in mm	
	CHIN 06 L		MFON 06 L25	
	MAPN 06 L32		MFVN 06 L25	
<ul style="list-style-type: none"> - kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12) 			MHON 06 L25	
			MHVN 06 L25	
dimensions shown are not binding and may be changed without notice				

Notes

Dimensions shown in mm are not binding and may be changed without notice.