

Part number

# MFVN 24 G32




Hood, LS-TYPE series, with 2 levers, M32 top cable entry without adapter, size "104.27", high construction

Product description		Material properties	
<b>Product type</b>	Hood	<b>Colour</b>	RAL 9005 black
<b>Series</b>	LS-TYPE	<b>RoHs conformity</b>	Compliant
<b>Closing type</b>	With 2 levers	<b>China RoHs - EFUP</b>	E
<b>Size</b>	Size "104.27"	<b>REACH SVHC substances</b>	No
<b>Cable entry</b>	Top cable entry M32	<b>Approvals / Standards</b>	
<b>Specification</b>	High construction	<b>Certifications</b>	DNV, BV
<b>Technical data</b>		<b>UL</b>	ECBT2
<b>IP degree of protection</b>	IP65 / IP66 / IP69	<b>cUL</b>	ECBT8
<b>Further technical details</b>		<b>General ordering information</b>	
<b>Weight</b>	360,00 g	<b>EAN13 code</b>	8015747187428
<b>Operating temperature range (min, max)</b>	-40°C...+125°C	<b>eCl@ss 8.1</b>	27440202
		<b>ETIM 7.0</b>	EC000437
		<b>Packaging Information</b>	
		<b>Sub-packaging weight</b>	1,80 kg
		<b>Sub-packaging description</b>	Plastic packaging
		<b>Sub-packaging quantity</b>	5 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747188173

# Part number MFVN 24 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "104.27"		LS-TYPE version																																		
<p>inserts: .....</p> <table border="0"> <tr> <td>CD .....</td> <td>64 poles + @</td> <td>51+53 *</td> </tr> <tr> <td>CDD .....</td> <td>108 poles + @</td> <td>64+66 *</td> </tr> <tr> <td>CQE .....</td> <td>46 poles + @</td> <td>83+85 *</td> </tr> <tr> <td>CSH .....</td> <td>24 poles + @</td> <td>91+93 *</td> </tr> <tr> <td>CCE .....</td> <td>24 poles + @</td> <td>100+104 *</td> </tr> <tr> <td>CNE, CSE, JCNE, JCSE</td> <td>24 poles + @</td> <td>101 and 109 *</td> </tr> <tr> <td>CSS .....</td> <td>24 poles + @</td> <td>121+123 *</td> </tr> <tr> <td>CMSE .....</td> <td>10+2 (aux) poles + @</td> <td>139 *</td> </tr> <tr> <td>CMCE .....</td> <td>10+2 (aux) poles + @</td> <td>139 *</td> </tr> <tr> <td>CX .....</td> <td>4/8 poles + @</td> <td>155 *</td> </tr> <tr> <td>MIXO .....</td> <td>6 modules</td> <td>160+195 *</td> </tr> </table> <p>insert centre distance: <b>104 x 27 mm</b> * refer to catalogue page CN.12</p>						CD .....	64 poles + @	51+53 *	CDD .....	108 poles + @	64+66 *	CQE .....	46 poles + @	83+85 *	CSH .....	24 poles + @	91+93 *	CCE .....	24 poles + @	100+104 *	CNE, CSE, JCNE, JCSE	24 poles + @	101 and 109 *	CSS .....	24 poles + @	121+123 *	CMSE .....	10+2 (aux) poles + @	139 *	CMCE .....	10+2 (aux) poles + @	139 *	CX .....	4/8 poles + @	155 *	MIXO .....	6 modules	160+195 *
CD .....	64 poles + @	51+53 *																																				
CDD .....	108 poles + @	64+66 *																																				
CQE .....	46 poles + @	83+85 *																																				
CSH .....	24 poles + @	91+93 *																																				
CCE .....	24 poles + @	100+104 *																																				
CNE, CSE, JCNE, JCSE	24 poles + @	101 and 109 *																																				
CSS .....	24 poles + @	121+123 *																																				
CMSE .....	10+2 (aux) poles + @	139 *																																				
CMCE .....	10+2 (aux) poles + @	139 *																																				
CX .....	4/8 poles + @	155 *																																				
MIXO .....	6 modules	160+195 *																																				
		hoods with 4 pegs		covers																																		
description		part no.	entry M	part no.																																		
with 2 levers and gasket, top entry		MHVN 24 G32	32	CHCN 24																																		
with 2 levers and gasket, top entry, high construction		MFVN 24 G32	32	CHCN 24 G																																		
covers with pegs				CHCN 24																																		
covers with 2 levers				CHCN 24 G																																		
dimensions in mm		dimensions in mm		dimensions in mm																																		
<p>MHVN 24 G32</p>		<p>CHCN 24</p>		<p>CHCN 24 G</p>																																		
<p>MFVN 24 G32</p>																																						
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>																																						
<p>dimensions shown are not binding and may be changed without notice</p>																																						

## Notes

Dimensions shown in mm are not binding and may be changed without notice.