

Part number

MHVN 16 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry, size "77.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 levers
Size	Size "77.27"
Cable entry	Top cable entry with adapter M32

Technical data

IP degree of protection	IP65 / IP66 / IP69
--------------------------------	--------------------

Further technical details

Weight	186,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194389
eCl@ss 8.1	27440202
ETIM 7.0	EC000437


Packaging Information

Sub-packaging weight	0,93 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747194396

Part number MHVN 16 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "77.27"		LS-TYPE version	
<p>inserts: page</p> <p>CD 40 poles + @ 49+52 *</p> <p>CDD 72 poles + @ 62+65 *</p> <p>CQE 32 poles + @ 82+84 *</p> <p>CSH 16 poles + @ 90+92 *</p> <p>CCE 16 poles + @ 98+102 *</p> <p>CNE, CSE, JCNE, JCSE 16 poles + @ 99 and 108 *</p> <p>CSS 16 poles + @ 120+122 *</p> <p>CMSE 6+2 (aux) poles + @ 137 *</p> <p>CMCE 6+2 (aux) poles + @ 136 *</p> <p>CP 6 poles + @ 149+150 *</p> <p>CX 6/36 e 12/2 poles + @ 152+153 *</p> <p>CX 4/0 e 4/2 poles + @ 154 *</p> <p>MIXO 4 modules 160+195 *</p> <p>insert centre distance: 77,5 x 27 mm</p> <p>* refer to catalogue page CN.12</p>					
		hoods with 4 pegs		covers	
description		part no.	entry	part no.	
with 2 levers and gasket, top entry		MHVN 16 G32	32	CHCN 16	
with 2 levers and gasket, top entry, high construction		MFVN 16 G32	32	CHCN 16 G	
cover with pegs				CHCN 16	
cover with 2 levers				CHCN 16 G	
		dimensions in mm		dimensions in mm	
		<p>MHVN 16 G32</p>		<p>CHCN 16</p>	
		<p>MFVN 16 G32</p>		<p>CHCN 16 G</p>	
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder</p> <p>- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>					
<p>dimensions shown are not binding and may be changed without notice</p>					

Notes

Dimensions shown in mm are not binding and may be changed without notice.