

Part number

MHVN 24.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry, size "104.27"

Product description

| | |
|---------------------|----------------------------------|
| Product type | Hood |
| Series | LS-TYPE |
| Closing type | With 4 pegs |
| Size | Size "104.27" |
| Cable entry | Top cable entry with adapter M32 |

Technical data

| | |
|--------------------------------|--------------------|
| IP degree of protection | IP65 / IP66 / IP69 |
|--------------------------------|--------------------|

Further technical details

| | |
|---|----------------|
| Weight | 170,00 g |
| Operating temperature range (min, max) | -40°C...+125°C |

Material properties

| | |
|------------------------------|----------------|
| Colour | RAL 9005 black |
| RoHs conformity | Compliant |
| China RoHs - EFUP | E |
| REACH SVHC substances | No |

Approvals / Standards

| | |
|-----------------------|---------|
| Certifications | DNV, BV |
| UL | ECBT2 |
| cUL | ECBT8 |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747194327 |
| eCl@ss 8.1 | 27440202 |
| ETIM 7.0 | EC000437 |


Packaging Information

| | |
|----------------------------------|-------------------|
| Sub-packaging weight | 0,85 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747194334 |

Part number MHVN 24.32



Catalogue drawings



Catalogue drawings

| CH..N - MA, MF..N enclosures | | size "104.27" | | LS-TYPE version | |
|--|--|---|------------|---------------------------|--|
| <p>inserts: page</p> <p>CD 64 poles + @ 51+53 *</p> <p>CT, CTS **) 64 poles + @ 57 *</p> <p>CDD 108 poles + @ 64+66 *</p> <p>CDE 46 poles + @ 83+85 *</p> <p>CSH 24 poles + @ 91+93 *</p> <p>CCE 24 poles + @ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS 24 poles + @ 122+123 *</p> <p>CTE, CTSE **) 24 poles + @ 129 *</p> <p>CMSE 10+2 (aux) poles + @ 139 *</p> <p>CMCE 10+2 (aux) poles + @ 138 *</p> <p>CX 4/8 poles + @ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p> | | <p> housings with double lever</p> | | <p> hoods with 4 pegs</p> | |
| description | part no. | entry M | part no. | entry M | |
| bulkhead mounting housing, with 2 levers | CHIN 24 | | | | |
| surface mounting housing, high construction, with 2 levers | MAPN 24.32 | 32 | | | |
| with pegs, side entry | | | MHON 24.32 | 32 | |
| with pegs, side entry, high construction | | | MFON 24.32 | 32 | |
| with pegs, side entry | | | MHVN 24.32 | 32 | |
| with pegs, side entry, high construction | | | MFVN 24.32 | 32 | |
| <p>**) only in the CHIN 24 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <p>dimensions shown are not binding and may be changed without notice</p> | <p>dimensions in mm</p> <p>CHIN 24</p> <p>MAPN 24.32</p> | <p>dimensions in mm</p> <p>MFON 24.32</p> <p>MFVN 24.32</p> <p>MHON 24.32</p> <p>MHVN 24.32</p> | | | |

Notes

Dimensions shown in mm are not binding and may be changed without notice.